

Polishing agent preparation- and supply device

NBT 10K

Machine Characteristics

- Electrical heating
- Cooling via internal coolant circuit / cooling compressor
- Electronic temperature control with setpoint setting and digital display
- Continuous media mixing in the storage tank
- All parts in contact with the medium are made of stainless steel or plastic
- Circulation of the temperature-controlled medium by means of an abrasion resistant pump
- Supply of several consumers is possible in parallel

Areas of application

- Circulation and cooling of liquids and suspensions with high temperature accuracy



Technical Details

	NBT 10K
Filling volume in l ca.:	10
Delivery pump:	1
Pump capacity in l/min:	max. 65
Temperature accuracy in °C:	≤ 1
Heating capacity in kW:	0,27
Compressor power in kW:	0,55
Connected load in V/Hz:	400 / 50
Power requirement in kW:	1,2
Weight in kg:	55
Dimensions (WxDxH) in mm:	480 x 830 x 520

Other versions on request.



STOCK KONSTRUKTION

Stock Konstruktion GmbH | Am Stollenbach 7-9 | 65623 Schiesheim-Zollhaus
Telephone: +49 (0) 6430-92391-0 | E-Mail: info@stock-konstruktion.de | www.stock-konstruktion.de

Version 03/2022