

# Polishing agent preparation- and supply unit

NB 45R / NB 65R

## Machine Characteristics

- Media mixing via gear motor and agitator
- All parts in contact with the medium are made of stainless steel or plastic
- Circulation of the medium by means of abrasion resistant pump
- Device consists of: removable lid, round container, mobile frame

## Areas of application

- Circulation and mixing of liquids and suspensions

## Options

- 2. Delivery pump
- Stand (see picture) for easy cleaning of the device



Option: Stand



Frame with wheels



Container

## Technical Details

	NB 45R	NB 65R
<b>Filling volume in l ca.:</b>	20 - 45	30 - 65
<b>Delivery pump:</b>	1	1
<b>Pump capacity in l/min:</b>	max. 65	max.65
<b>Connected load in V/Hz:</b>	400 / 50	400 / 50
<b>Power requirement in kW:</b>	1,5	1,5
<b>Weight in kg:</b>	25	35
<b>Dimensions (WxDxH) in mm:</b>	600 x 600 x 500	700 x 700 x 500

Other versions on request.



STOCK KONSTRUKTION

Stock Konstruktion GmbH | Am Stollenbach 7-9 | 65623 Schiesheim-Zollhaus  
Telephone: +49 (0) 6430-92391-0 | E-Mail: info@stock-konstruktion.de | www.stock-konstruktion.de

Version 03/2022