

# Lapping- and Polishing machine

## manual

MS 400

### Machine Characteristics

- One spindle processing Machine without lever
- Motorized spindle drive
- Individually variable spindle speed adjustment on potentiometer
- On and off of the motor via pedal and hand switch
- Basin and splash guard
- Spindle lock

### Application

- Manual lapping and polishing

### Option

- Work light
- Large table top with stainless steel cover and from stainless steel



### Technical Details

	<b>MS 400</b>
<b>Working diameter in mm (inch):</b>	max. 400 (15.75")
<b>Basin size in mm (inch):</b>	600 (23.62")
<b>Splash guard in mm (inch):</b>	Ø 600 (23.62")
<b>Distance:</b>	
<b>Spindle lift distance – centre table in mm (inch):</b>	80 (3.15")
<b>Spindle speed in min<sup>-1</sup>:</b>	40 – 600
<b>Spindle connection thread DIN 58725:</b>	M27
<b>Power requirement in kW:</b>	3,0
<b>Dimensions in mm (W x D x H):</b>	1180 x 1080 x 1360
<b>Weight in kg:</b>	295
<b>Paint finish (standard):</b>	Light grey RAL 7035

Tools and accessories can be found in our current catalogue or on request.



STOCK KONSTRUKTION

Stock Konstruktion GmbH | Am Stollenbach 7-9 | 65623 Schiesheim-Zollhaus - Germany  
Telephone: +49 (0) 6430-92391-0 | E-Mail: [info@stock-konstruktion.de](mailto:info@stock-konstruktion.de) | [www.stock-konstruktion.de](http://www.stock-konstruktion.de)

Vers. 09/2022