

# Lapping and Polishing Machine

## Manuel and pedal



STOCK KONSTRUKTION GMBH

### NLP 400 M

#### Machine characteristics

- One spindle processing Machine
- Motorized spindle drive
- Individually variable spindle speed adjustment on potentiometer
- On and off of the motor via pedal
- Spindle lock for tool change
- Plastic basin

#### Options

- Splash guard ring obliquely tapering upward, Ø 600 mm, approx. 70 mm high
- Multifunctional foot switch: brake, accelerate, start-stop

#### Application

- Manual lapping and fine polishing
- Facet
- Dressing up of tools



fig. NLP 400 M

#### Technical details

Working diameter in mm (inch):

Basin size in mm(inch):

Distance:

Spindle lift distance – centre table in mm (inch):

Spindle speed in  $\text{min}^{-1}$ :

Spindle connection thread DIN 58725 in M:

Power requirement in kW:

Dimensions in mm (inch) (w x l x h):

Weight in kg (lbs):

Paint finish:

#### NLP 400 M

max. 400 (15.75") Ø

600 (23.62") Ø

80

20 – 300

398

2,0

1240 (48.82") x 1100 (43.31") x 1400 (55.12")

285 (639)

Standard light grey RAL 7035

Tools and accessories can be found in our current catalogue or on request.

Stock Konstruktion GmbH, Am Stollenbach 7-9, 65623 Schiesheim-Zollhaus; Germany

Phone: ++49 (0) 6430-9250448

Fax ++49 (0) 6430-9250453

email: [info@stock-konstruktion.de](mailto:info@stock-konstruktion.de) [www.stock-konstruktion.de](http://www.stock-konstruktion.de)

Rev. 01/2015